

PANEL Printer

3inch printer *Porti-P340*



Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec, MAX)
- UART or TTL interface.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.

Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems

Specifications

Item	Specification
Printing method	Direct thermal line printing
Characters per line	64 cpl
Characters size	Eng : 9*24 dots, 12*24 dots / Kor : 16*24 dots [24*24 dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	3-inch (72 mm, 576 dots)
Paper speed	50 mm/sec (MAX)
Paper supplied	Thermal roll paper (80mm wide, 40Ø)
Dimensions	110 * 77.7 * 48 mm
Weight	300g
Interface	UART or TTL
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Receive buffer size	10K bytes
Input power	9VDC, Standby 60mA and Max 3A